

LD PUMPED ALL-SOLID-STATE Q-SWITCHED LASER AT 660 nm

RN-III-660/1~2uJ/1-5mW

产品描述

All solid state Q-switched laser at 660 nm has the features of high peak power, high repetition rate, and short pulse duration, which is widely used in medical, scientific research, industry, etc

产品参数

RN-III-660/1~2uJ/1-5mW		
Central wavelength (nm)	660±1	
Operating mode	Q-switched pulsed laser	
Single pulse energy (μJ)	1~2	
Pulse duration (ns)	~15	
Peak power (W)	70~130	
Rep. rate (kHz)	FIXED	Setting up one fixed rep. rate internal between 1kHz-2kHz with stable pulse energy, pulse duration and pulse period.
	EXT TRIG	1kHz-2kHz by external trigger with stable pulse energy, pulse duration and pulse period.
	QCW	QCW state with one rep. rate between 2k-3kHz
Average power (mW)	Average power (mW) = Single pulse energy (μJ) * Rep. rate (kHz)	
Ave power stability (over 4 hours)	<3%, <5%	
Transverse mode	TEM ₀₀	
Warm-up time (minutes)	<10	
M ² factor	<1.2	
Beam divergence, full angle (mrad)	<1.5	
Beam diameter at 1/e ² (mm)	~1.2	
Beam height from base plate (mm)	24.8	
Operating temperature (°C)	10~35	
Power supply (90-264VAC)	PSU-III-FDA	
Expected lifetime (hours)	10000	
Warranty period	1 year	