

## LOW NOISE INFRARED DIODE LASER AT 830nm

RN-III-830/1~2000mW

### 产品描述

It features ultra compact design, long lifetime, cost-effectiveness and easy operation. They are widely used in measurement, spectrum analysis, etc.

### 产品参数

RN-III-830/1~2000mW		
Central wavelength (nm)	830±10	
Operating mode	CW	
ASE Output power (mW)	>1, 100, 200, 300, ..., 2000	
Power stability (rms, over 4 hours)	<1%, <2%, <3% (<0.5%, optional)	
Transverse mode	Multimode	
Noise of amplitude(rms,20Hz~20MHz)	<1%	
Dimensions of beam at the aperture (mm)	~5×8	
Beam divergence, full angle (mrad)	<2.5	
Warm-up time (minutes)	<5	
Beam height from base plate (mm)	24.5	
Operating temperature (°C)	10~35	
Power supply	85-264VAC	PSU-III-LED/PSU-III-FDA (Frequency for 1Hz-30kHz)
	100-240VAC	PSU-A-D (Frequency for 30kHz -100kHz)
TTL / Analog modulation	TTL or Analog with 1Hz-1kHz 1kHz-10kHz, 10kHz-30kHz optional	
Expected lifetime (hours)	10000	
Warranty	1 year	