

LD PUMPED ALL-SOLID-STATE GREEN LASER AT 532nm

RN-FN-532/1~1500mW



产品描述

All solid state 532nm green laser is made features of high output power stability, good beam profile, ultra compact, long lifetime, low cost and easy operating, which is widely used in collimation, laser medical treatment, scientific experiment, optical instrument, etc.

产品参数

RN-FN-532/1~1500mW	
Wavelength (nm)	532±1
Operating mode	CW
Output power (mW)	>1, 5, 10, 20, ... , 1000 >1000, 1100, ..., 1500
Power stability (rms, over 4 hours)	<1%, <2%, <3% <2%, <3%
Transverse mode	TEM ₀₀
M ² factor	<1.2(<1.1 optional) <1.2
Beam diameter at the aperture (1/e ² mm)	~2.0
Beam divergence, full angle (mrad)	<1.5
Beam height from base plate (mm)	27.4
Polarization ratio	>100:1 Horizontal±5 degree (Vertical Optional)
Warm-up time (minutes)	<10
Pointing stability after warm-up (mrad)	<0.05
Operating temperature (°C)	10~35
Power supply (90-264VAC)	PSU-H-LED/PSU-H-FDA/PSU-SR
Modulation option	TTL on/off, 1Hz-1KHz, 1KHz-10KHz, 10KHz-30KHz; and Analog modulation option
Expected lifetime (hours)	10000
Warranty	1 year